

YOGI VEMANA UNIVERSITY :: KADAPA

Dr. Y. Nazeer Ahammed
REGISTRAR I/c

Office Phone: 08562-225429, Fax: 225419

Mail: registraryvu@gmail.com

Web: www.yogivemanauniversity.ac.in

No. YVU/DEVP/ Bio-Metric Machines/2015-16

Date: 05-12-2015

To

The Firms,

Sir/Madam,

Sub:- Yogi Vemana University, Kadapa - Development – ID card Printer & Bio-Metric Machine – Purchase of items - Call for quotations- Regd.

Sealed quotations through registered post/ speed post/courier/drop box in favor of **The Registrar , Yogi Vemana University, KADAPA, 516 003**, with details of specifications for the following items are invited so as to reach the undersigned on or before **12.12.2015**. The quotations must accompany the relevant terms and conditions.

S. No.	Item	Specifications
1	Bio and Card attendance Machine (ESSL X 990)	Specifications: 3000 FP Templates; Transaction Storage: 100000; Communications: TCP/IP, USB, RS232, RS485; Processor: 32 Bit; Identification time: ≤ 2 seconds; FAR: $\leq 0.0001\%$; FRR: $\leq 1\%$; Operating Temperature: $0^{\circ}\text{C} - 45^{\circ}\text{C}$; Operating: 20%-80%; Sensor: OEM Optical Sensor 500 DPI; Power Supply: 12V DC; Card reader: EM RFID(Proximity), Mifare , HID(Optional); Access Control Interface: 3rd party electric lock, door sensor, exit button, alarm, Door Bell; Standard Function:Work code, DLST, Anti-Pass Back; Optional Function: Web Server, WiFi, GPRS, CDMA; Wigand Signal:Input & Output; Display:3.5 Inch TFT Screen; Alogrithm Version:9.0/10.0; Dimension (WxHxD):215 X 145 X 35 mm; Language:English
2	Bio and Card attendance Machine (ESSL X 990)	Specifications: 5000 FP Templates; Transaction Storage: 100000; Communications: TCP/IP, USB, RS232, RS485; Processor: 32 Bit; Identification time: ≤ 2 seconds; FAR: $\leq 0.0001\%$; FRR: $\leq 1\%$; Operating Temperature: $0^{\circ}\text{C} - 45^{\circ}\text{C}$; Operating: 20%-80%; Sensor: OEM Optical Sensor 500 DPI; Power Supply: 12V DC; Card reader: EM RFID(Proximity), Mifare , HID(Optional); Access Control Interface: 3rd party electric lock, door sensor, exit button, alarm, Door Bell; Standard Function:Work code, DLST, Anti-Pass Back; Optional Function: Web Server, WiFi, GPRS, CDMA; Wigand Signal:Input & Output; Display:3.5 Inch TFT Screen; Alogrithm Version:9.0/10.0; Dimension (WxHxD):215 X 145 X 35 mm; Language:English
3	Technical support (quote cost for each item)	Commissioning of equipment (LAN and Power), Software installation. The supplier must maintain and have to provide consolidation reports periodically


REGISTRAR 5/12/15